








HIKVISION





IP Camera

No.	Model	Appearance	Description	Price
2 Line Series				
1	DS-2CD2020F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE	4.750.000 IRR
2	DS-2CD2022WD-I		1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	5.750.000 IRR
3	DS-2CD2042WD-I		1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+	6.400.000 IRR
4	DS-2CD2052-I		1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, H.264+ Optimized Codec	7.880.000 IRR
5	DS-2CD2120F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage	4.750.000 IRR
6	DS-2CD2120F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), -S: Audio/Alarm I/O connectors	5.160.000 IRR
7	DS-2CD2122FWD-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec	5.750.000 IRR
8	DS-2CD2122FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+ Optimized Codec/ -S: Audio/Alarm I/O	6.160.000 IRR
9	DS-2CD2142FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm I/O”	6.700.000 IRR
10	DS-2CD2152F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, H.264+-S: Audio/Alarm I/O”	8.300.000 IRR






Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
11	DS-2CD2322WD-I		1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6/8/12mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+ Optimized Codec	6.550.000 IRR
12	DS-2CD2342WD-I		1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+	7.230.000 IRR
13	DS-2CD2352-I		1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m, H.264+	8.710.000 IRR
14	DS-2CD2420F-IW		"1/3"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, -W: Built-in Wi-Fi with WPS"	4.750.000 IRR
15	DS-2CD2422FWD-IW		1/2.8" Progressive CMOS, ICR, ICR, 0.01lux/F1.2, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, built-in WIFI, H.264+	5.870.000 IRR
16	DS-2CD2442FWD-IW		1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, built-in WIFI, H.264+ Optimized Codec	6.520.000 IRR
17	DS-2CD2520F		1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Vandal-proof IK10,	4.510.000 IRR
18	DS-2CD2522FWD-I		"1/2.8"" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), H.264+	7.880.000 IRR
19	DS-2CD2542FWD-IS		"1/3"" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), H.264+-S: Audio/alarm I0	9.000.000 IRR





Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
20	DS-2CD2620F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included),	8.180.000 IRR
21	DS-2CD2620F-IZ		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included),-Z:Motorized VF lens”	9.660.000 IRR
22	DS-2CD2622FWD-IS		“1/2.8” Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO	11.860.000 IRR
23	DS-2CD2642FWD-IS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO	13.520.000 IRR
24	DS-2CD2642FWD-IZS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ -S: Audio/alarm IO/-Z: Motorized VF lens”	15.930.000 IRR
25	DS-2CD2652F-IS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+-S: Audio/alarm IO	16.700.000 IRR
26	DS-2CD2652F-IZS		“1/3” Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+/-S: Audio/alarm IO/-Z: Motorized VF lens”	18.740.000 IRR
27	DS-2CD2720F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof”	8.470.000 IRR
28	DS-2CD2720F-IZ		“1/3” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof,-Z:Motorized VF lens”	9.830.000 IRR
29	DS-2CD2722FWD-IS		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO	12.110.000 IRR



Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
30	DS-2CD2742FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+-S: Audio/alarm IO	13.770.000 IRR
31	DS-2CD2742FWD-IZS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+-S: Audio/alarm IO/-Z: Motorized	16.190.000 IRR
32	DS-2CD2752F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO	17.090.000 IRR
33	DS-2CD2752F-IZS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, H.264+ -S: Audio/alarm IO/-Z: Motorized VF lens”	19.000.000 IRR
34	DS-2CD2232-IS		1/3” Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 6mm/F2.0 lens (4mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 50m, Bracket included	7.770.000 IRR
35	DS-2CD2332-I		1/3” Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	6.933.000 IRR
36	DS-2CD2632F-I		“1/3” Progressive CMOS, ICR, 0.1lux/F1.2, 2048x1536:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, On-board card slot (up to 64GB), Support mobile monitoring via HIK-cloud P2P	10.800.000 IRR
37	DS-2CD2732F-I		“1/3” Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, On-board card slot (up to 64GB), Vandal-proof housing, Support mobile monitoring via HIK-cloud P2P	11.000.000 IRR

Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
38	DS-2CD2T22WD-I3		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -3: 1pcs EXIR LED, up to 30m IR range”	6.900.000 IRR
39	DS-2CD2T22WD-I5		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -5: 2pcs EXIR LEDs, up to 50m IR range	7.210.000 IRR
40	DS-2CD2T42WD-I5		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ -15: 2pcs EXIR LEDs, up to 50m IR range	8.040.000 IRR
41	DS-2CD2T52-I5		1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, H.264+ , 2pcs EXIR LEDs, up to 50m IR range	9.900.000 IRR
42	DS-2CD2942F-IS		“1/3” Progressive CMOS, Electronic Day/night, Up to 2464 x 1520 resolution, 1.6mm/F1.6 fixed lens, 180° Panoramic view, H.264/MJPEG, 3D DNR, DC12V & PoE, Support on-board storage up to 64GB, software de-warping via iVMS5200 or iVMS4200, -I: 3pcs IR LEDs, up to 10m IR/-S: Audio/Alarm IO	16.690.000 IRR
43	DS-2CD2F22FWD-IS		“1/2.8” Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included),-S: Audio/alarm	7.590.000 IRR
44	DS-2CD2F42FWD-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 1920x1080: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+ Optimized Codec, H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB (SD card not included), Pan:0° ~180°, Tilt: 0°~75°, -S: Audio/Alarm IO	8.420.000 IRR
45	DS-2CD2F52F-IS		“1/3” Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+ Optimized Codec, H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, -S: Audio/Alarm IO”	10.430.000 IRR
46	DS-2CD2E20F-W		“1/3” Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Color Lens Cover optional -W: Built-in Wi-Fi”	6.460.000 IRR

Network Camera

No.	Model	Appearance	Description	Price
2 Line Series				
47	DS-2CD2Q10FD-IW		1/4" Progressive CMOS, ICR, 0lux with IR, 4mm, Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection,	6.820.000 IRR
48	DS-2CD2D14WD		1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC,	5.340.000 IRR

HIKVISION®
First Choice for Security Professionals

نماینده رسمی شرکت پارس ارتباط

